



Modul-System Ambient/Workbench Light

Technical specification

Part number Description	19701-03 / 19701-032 Ambient/Workbench light 324	19702-03 / 19702-032 Ambient/Workbench light 648	19703-03 Ambient/Workbench light 972
Total length (mm)	334	658	982
Total width (mm)	38		
Total height (mm)	13		
Weight (g)	127	262	381
Power supply (Vdc)	12		
Power (W)	4	8	12
Amp draw (A)	0.34	0.67	1
Lumens (lm)	230	500	890
Color temperature (K)	4300		
Light spread angle	120°		
Cable length (mm)	2000		
Installation	2x screws or rivets 4,8 mm.		
Mtrl specification - housing	Aluminum, polycarbonate, polypropylene.		
IC	IC is a "constant current source". This means that the LED brightness will stay constant, even when the power supply fluctuates (interval of 11-16V).		
EMC	Tested for electromagnetic compatibility (EMC) according to UN ECE Regulation No. 10.04. 04.		
ESD	Tested for immunity to electrostatic discharge (ESD). ESD tests according to EN 61000-4-2.		
CE	CE marked. Tests were based on EN 50498:2010, product family standard for aftermarket electronic equipment in vehicles and additional RF immunity tests according to UN ECE Regulation No. 10.04. 04.		